



290DEX



NOTE: ALL LEADS 9" OUT MIN., STRIPPED .5"



DIMENSIONS:

A	3.438" ±0.063
B	4.063" ±0.125
C	4.125" ±0.063
D	1.844" ±0.063
E	2.750" ±0.063
F	3.438" ±0.063

ELECTRICAL DATA:

Turns ratio:	1 : 2.96 (RED - RED)	
Exciting Current	@ 240V, 50Hz, BLK - BLK = 266mA	Max.
DCR	@ 20C, BLK - BLK = 5.059 Ω	±20%
	@ 20C, RED - RED = 74.40 Ω	±20%
	@ 20C, YEL - YEL = 0.111 Ω	±20%
	@ 20C, GRN - GRN = 0.058 Ω	±20%
Pri. Voltage	240V	
Sec. Voltage	650VCT 200mA DC C/W 50V TAP, 5V 3A / 6.3VCT 4A	
No Load Voltage	712.29VCT/ 5.30V / 6.75V	
Power	197 WATTS	

HAMMOND ELECTRONICS
 52 RANKIN PLACE,
 WATERLOO, ONTARIO, N2L 3Z5.
 PHONE (519) 886-6181
 FAX # (519) 886-9540

TITLE		290DEX	
			DR BY IOAN POP
0	05/12/09	PRELIMINARY.	I.P. DATE 05/12/09
NO	DATE	REVISION	DIM IN(X)MM()

290DEX